

# FiberFlo® FPNN All-Nylon Pleated Cartridge Filters

- ✓ Absolute rated
- ✓ Long service life
- ✓ All Nylon Construction for Maximum Chemical Compatibility
- ✓ Homogenous high purity media
- ✓ Rigorous quality standards
- ✓ Integrity testable in the field

FiberFlo "NN" All-Nylon cartridges are absolute rated. Made with Nylon membrane, cage, core, end caps and support media, the cartridges have high surface area with excellent flow rates per 10 inch length. Their single-material construction gives them broad compatibility with a wide range of chemicals. The physiological inertness of Nylon makes them suitable for the filtration of a number of chemicals, including Photo Resists, Developers and Solvents.

## Applications

- Final filtration for chemical distribution
- Photo Resists and Developers
- Plating solutions
- Magnetic coatings

## Dependable Performance


FiberFlo "NN" cartridges consist of a nylon membrane with thermally bonded nylon components to provide a very durable product with only one material of construction.

The hydrophilic nylon membrane contains no surfactants or surface wetting agents. Manufactured under QSR, the filters are 100% integrity tested in manufacturing to ensure consistent and reliable performance.

Absolute ratings for FiberFlo "NN" cartridges can be verified in the field by integrity testing using bubble point or diffusional flow testing.

All FiberFlo "NN" cartridges pass USP Class VI plastics tests as well as tests for cytotoxicity, hemolysis and pyrogenicity.

## Typical Water Flow Rate (per 10" length)



**MAR COR**<sup>®</sup>  
**PURIFICATION**  
A Cantel Medical Company



Specifications	
Filter Media:	Pleated Nylon Membrane
Membrane Support, Core Tube and End Caps:	Nylon
Sealing Technology:	Thermal Bonding
Endotoxins:	Less than 0.5 EU/ml
Biosafety:	All components meet or exceed USP Class VI-121 °C plastic tests
FDA Materials:	All components meet the FDA requirements for food contact according to 21 CFR 177-182
Oxidizable Substances:	Filtrate meets or exceeds USP XXI requirements for purified water after 1 liter flush
O-Ring:	Silicone Standard (Other Elastomers available)
O-Ring Color:	Silicone Red (Other elastomers vary)

Recommended Integrity Test	
Pore Size	Diffusional Flow (cc/min @ Test Pressure) per 10" Length
0.03 $\mu\text{m}$	< 55 @ 60 psig (4.1 bar)
0.1 $\mu\text{m}$	< 55 @ 48 psig (3.3 bar)
0.2 $\mu\text{m}$	< 55 @ 35 psig (2.4 bar)
0.45 $\mu\text{m}$	< 55 @ 20 psig (1.4 bar)
0.65 $\mu\text{m}$	< 55 @ 15 psig (1.0 bar)
1.0 $\mu\text{m}$	< 55 @ 8 psig (0.6 bar)

Maximum Operating Pressure	
120 psi (7 bar) at inlet	
Maximum Differential Pressure	
Forward Flow	50 p.s.i. (4.1 bar) pressure drop at 68 °F (20 °C)
Reverse Flow	40 psi (2.7 bar) pressure drop at 68 °F (20 °C)

Sanitization / Sterilization	
Hot Water	Hot Water Flush – Up to 90 °C
Chemical Sanitization	Standard concentrations of Minncare® Cold Sterilant, hydrogen peroxide and other chemicals.

Cartridge Dimensions	
Nominal Length *	Filtration Area
10 inch	6.5 ft <sup>2</sup> / 0.5 M <sup>2</sup>
20 inch	13.0 ft <sup>2</sup> / 1.0 M <sup>2</sup>
30 inch	19.5 ft <sup>2</sup> / 1.5 M <sup>2</sup>
40 inch	26.0 ft <sup>2</sup> / 2.0 M <sup>2</sup>

Outside Diameter: 2.77 in / 7 cm

\* Actual overall length of cartridge will vary depending on configuration. Cartridge performance is as specified regardless of configuration.

#### Product Ordering Information

FiberFlo FPNN Nomenclature Matrix

FPNN - 003 - 20 - A - V

#### Pore Size Rating

003 - 0.03 $\mu\text{m}$	01 - 0.1 $\mu\text{m}$	02 - 0.2 $\mu\text{m}$
045 - 0.45 $\mu\text{m}$	065 - 0.65 $\mu\text{m}$	1 - 1.0 $\mu\text{m}$

#### Length

10 - 10 inch	20 - 20 inch	30 - 30 inch
40 - 40 inch		

#### End Adapter Code

A - 222/flat	B - 222/fin	C - 226/fin
D - DOE Flat Gasket	E - Internal O-Ring/flat	

#### Elastomer

Blank - Silicone	V - Viton	T - Teflon encapsulated Viton
------------------	-----------	-------------------------------



**MAR COR PURIFICATION**  
A Cantel Medical Company

Mar Cor Purification  
4450 Township Line Road  
Skipack, PA 19474-1429  
U.S.A.  
Tel: (484) 991-0220  
Toll Free: (800) 346-0365  
Fax: (484) 991-0230

Mar Cor Purification  
14605 28th Avenue North  
Minneapolis, MN 55447-4822  
U.S.A.  
Tel: (763) 553-3300  
Toll Free: (800) 328-3370  
Fax: (763) 553-3387

Mar Cor Purification  
3250 Harvester Road - Unit 6  
Burlington, ON L7N 3W9  
Canada  
Tel: (905) 639-7025  
Toll Free: (800) 268-5035  
Fax: (905) 639-0425

Minntech B.V.  
Sourethweg 11  
6422 PC Heerlen  
The Netherlands  
Tel: (+31) 45 5471 471  
Fax: (+31) 45 5429 695

Minntech Asia/Pacific Pte. Ltd  
438 Alexandra Road  
#03-01 Alexandra Point  
Singapore 119958  
Tel: (+65) 6227 9698  
Fax: (+65) 6225 6848

www.mcpor.com